


SMALLEY® SPIRAL RETAINING RINGS

Acciaio al Carbonio per Molle
SAE 1060-75

surface treatment:
Oliatura

Esempio di designazione: FHE-0050



d1=diametro foro
d2=diametro gola
d3=diametro esterno
S=spessore

Heavy duty
series
FHE - per fori
(in pollici)



description	Price Euro x100	% Price Change		Package
		1	2	
FHE-0081	89,00	+ 20%	-	1000

DESCRIPTION	GROOVE	THRUST CAPACITY
FHE-0081	d2 inch. 0.852 mm 21.64	ring shear Newtons 16.791 L.B.S. 3,775
d1 mm 20.62	Toll. d2 inch. +0,005 mm +0,130	(safety factor =3)
d1 inch 0.812	c inch. 0.043 mm 1.09	groove yield Newtons 5.106 L.B.S. 1,148
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,006 mm +0,150	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 0.860 mm 21.84		
Toll. d3 inch. +0,013 mm +0,33		
b inch. 0.075 mm 1.91		
Toll. b inch. +/-0,004 mm +/-0,10		
s inch. 0.037 mm 0.94		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 0.71		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350