


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XAH-37

Medium duty
series
**XAH - for bores
(in inches)**


description	Price Euro x100	% Price Change		Package
		1	2	
XAH-185	98,00	+ 20%	-	100

DESCRIPTION	GROOVE	THRUST CAPACITY
XAH-185	d2 inch. 1.946 mm 49.43	ring shear Newtons 57.959 L.B.S. 13,030
d1 mm 46.99	Toll. d2 inch. +/-0,005 mm +/-0,13	(safety factor =3)
d1 inch 1.850	c inch. 0.068 mm 1.73	groove yield Newtons 27.920 L.B.S. 6,277
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,004 mm +0,100	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 1.975 mm 50.17		
Toll. d3 inch. +0,046 mm +1,17		
b inch. 0.156 mm 3.96		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.062 mm 1.57		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 7.19		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350