

SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: XDS-50



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Light duty series
XDS - for shafts
(in inches)



description	Price Euro x100	% Price Change		Package
		1	2	
XDS-650	830,00	+ 20%	-	25

DESCRIPTION	GROOVE	THRUST CAPACITY
XDS-650	d2 inch. 6.340 mm 161.04	ring shear Newtons 294.288 L.B.S. 66,162
d1 mm 165.10	Toll. d2 inch. +/-0,008 mm +/-0,2	(safety factor =3)
d1 inch 6.500	c inch. 0.103 mm 2.62	groove yield Newtons 163.494 L.B.S. 36,757
RING IN THE UNSTRESSED STATE		(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 6.270 mm 159.26	Toll. c inch. +0,005 mm +0,130	
Toll. d3 inch. -0,125 mm -3,18		
b inch. 0.250 mm 6.35		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.093 mm 2.36		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 60.58		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350