


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: WST-46

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
s=thickness

Carichi medio -
pesanti
WST - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
WST-87	22,00	+ 20%	-	500

DESCRIPTION	GROOVE	THRUST CAPACITY
WST-87	d2 inch. 0.835 mm 21.21	ring shear Newtons 23.619 L.B.S. 5,310
d1 mm 22.23	Toll. d2 inch. +/-0,003 mm +/-0,08	(safety factor =3)
d1 inch 0.875	c inch. 0.046 mm 1.17	groove yield Newtons 5.516 L.B.S. 1,240
RING IN THE UNSTRESSED STATE		(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 0.827 mm 21.01	Toll. c inch. +0,003 mm +0,080	
Toll. d3 inch. -0,013 mm -0,33		
b inch. 0.075 mm 1.91		
Toll. b inch. +/-0,004 mm +/-0,10		
s inch. 0.042 mm 1.07		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 1.00		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Produzione e distribuzione
fasteners, elementi di
fissaggio e lavorazioni
meccaniche

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Uffici Commerciali
250@gandini.it
tel +39 02 241 047 250

Amministrazione
350@gandini.it
tel +39 02 241 047 350