

SMALLEY® SPIRAL RETAINING RINGS
SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped
Example of designation: WH-50


d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Carichi medi
WH - for bores
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
WH-193	52,00	+ 20%	-	100

DESCRIPTION	GROOVE	THRUST CAPACITY
WH-193	d2 inch. 2.005 mm 50.93	ring shear Newtons 55.733 L.B.S. 12,530
d1 mm 49.23	Toll. d2 inch. +/-0,005 mm +/-0,13	(safety factor =3)
d1 inch 1.938	c inch. 0.056 mm 1.42	groove yield Newtons 20.728 L.B.S. 4,660
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,004 mm +0,100	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 2.025 mm 51.44		
Toll. d3 inch. +0,020 mm +0,51		
b inch. 0.118 mm 3.00		
Toll. b inch. +0,003/-0,005 mm +0,08/-0,13		
s inch. 0.049 mm 1.24		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 4.26		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Produzione e distribuzione
fasteners, elementi di
fissaggio e lavorazioni
meccaniche

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Uffici Commerciali
250@gandini.it
tel +39 02 241 047 250

Amministrazione
350@gandini.it
tel +39 02 241 047 350