


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WHM-25


d1=shaft diameter
d2=groove diameter
d3=external ring diameter
s=thickness

Heavy duty series
WHM - for bores (in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
WHM-237	130,00	+ 20%	-	100

DESCRIPTION	GROOVE	THRUST CAPACITY
WHM-237	d2 inch. 2.517 mm 63.93	ring shear Newtons 108.709 L.B.S. 24,440
d1 mm 60.33	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 2.375	c inch. 0.086 mm 2.18	groove yield Newtons 53.020 L.B.S. 11,920
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 2.535 mm 64.39		
Toll. d3 inch. +0,025 mm +0,64		
b inch. 0.200 mm 5.08		
Toll. b inch. +0,004/-0,006 mm +0,10/-0,15		
s inch. 0.078 mm 1.98		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 14.53		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350