


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WHT-50



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Medium-heavy
duty series
**WHT - for bores
(in inches)**



description	Price Euro x100	% Price Change		Package
		1	2	
WHT-206	100,00	+ 20%	-	100

DESCRIPTION	GROOVE	THRUST CAPACITY
WHT-206	d2	ring shear
d1 mm 52.37	inch. 2.175	Newtons 94.387
d1 inch 2.062	mm 55.25	L.B.S. 21,220
	Toll. d2	(safety factor =3)
	inch. +/-0,006	
	mm +/-0,15	
	c	groove yield
	inch. 0.086	Newtons 36.963
	mm 2.18	L.B.S. 8,310
	Toll. c	(based on a groove material yield strength of 310/mm and a safety factor of 2)
	inch. +0,005	
	mm +0,130	
RING IN THE UNSTRESSED STATE		
d3	inch. 2.190	
	mm 55.63	
Toll. d3	inch. +0,025	
	mm +0,64	
b	inch. 0.141	
	mm 3.58	
Toll. b	inch. +/-0,004	
	mm +/-0,1	
s	inch. 0.078	
	mm 1.98	
Toll. s	inch. +/-0,003	
	mm +/-0,08	
Weight Kg/1000	8.74	

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350