


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: WHT-50

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Medium-heavy
duty series
WHT - for bores
(in inches)


description	Price Euro x100	% Price Change	Package
WHT-275	150,00	+ 20%	100

DESCRIPTION	GROOVE	THRUST CAPACITY
WHT-275	d2 inch. 2.900 mm 73.66	ring shear Newtons 142.959 L.B.S. 32,140
d1 mm 69.85	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 2.750	c inch. 0.103 mm 2.62	groove yield Newtons 64.852 L.B.S. 14,580
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 2.921 mm 74.19		
Toll. d3 inch. +0,025 mm +0,64		
b inch. 0.188 mm 4.78		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.093 mm 2.36		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 18.53		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350