


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WHT-50



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Medium-heavy
duty series
WHT - for bores
(in inches)



description	Price Euro x100	% Price Change	Package
WHT-87	20,00	+ 20%	500

DESCRIPTION	GROOVE	THRUST CAPACITY
WHT-87	d2	ring shear
d1 mm	inch. 0.922	Newtons 23.619
d1 inch	mm 23.42	L.B.S. 5,310
	Toll. d2	(safety factor =3)
	inch. +/-0,003	
	mm +/-0,08	
	c	groove yield
	inch. 0.046	Newtons 6.583
	mm 1.17	L.B.S. 1,480
	Toll. c	(based on a groove material yield strength of 310/mm and a safety factor of 2)
	inch. +0,003	
	mm +0,080	
RING IN THE UNSTRESSED STATE		
d3	inch. 0.929	
	mm 23.60	
Toll. d3	inch. +0,013	
	mm +0,33	
b	inch. 0.065	
	mm 1.65	
Toll. b	inch. +/-0,004	
	mm +/-0,1	
s	inch. 0.042	
	mm 1.07	
Toll. s	inch. +/-0,002	
	mm +/-0,05	
Weight Kg/1000	0.91	

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350