


**SMALLEY® SPIRAL RETAINING RINGS**
**SAE 1070-90 Carbon Steel**

surface treatment:  
**Oil dipped**
**Example of designation: VH-25**

**Light duty series  
VH - for bores  
(in inches)**

**d1**=shaft diameter  
**d2**=groove diameter  
**d3**=external ring diameter  
**S**=thickness

| description   | Price<br>Euro x100 | % Price Change |   | Package |
|---------------|--------------------|----------------|---|---------|
|               |                    | 1              | 2 |         |
| <b>VH-181</b> | <b>35,00</b>       | + 20%          | - | 250     |

| DESCRIPTION                                 | GROOVE                                       | THRUST CAPACITY                                                                |
|---------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------------|
| VH-181                                      | <b>d2</b> inch. 1.869<br>mm 47.47            | <b>ring shear</b> Newtons 32.960<br>L.B.S. 7,410                               |
| <b>d1 mm</b> 46.02                          | <b>Toll. d2</b> inch. +/-0,005<br>mm +/-0,13 | (safety factor =3)                                                             |
| <b>d1 inch</b> 1.812                        | <b>c</b> inch. 0.039<br>mm 0.99              | <b>groove yield</b> Newtons 16.502<br>L.B.S. 3,710                             |
| <b>RING IN THE UNSTRESSED STATE</b>         | <b>Toll. c</b> inch. +0,003<br>mm +0,080     | (based on a groove material yield strength of 310/mm and a safety factor of 2) |
| <b>d3</b> inch. 1.890<br>mm 48.01           |                                              |                                                                                |
| <b>Toll. d3</b> inch. +0,020<br>mm +0,51    |                                              |                                                                                |
| <b>b</b> inch. 0.118<br>mm 3.00             |                                              |                                                                                |
| <b>Toll. b</b> inch. +/-0,004<br>mm +/-0,1  |                                              |                                                                                |
| <b>s</b> inch. 0.031<br>mm 0.79             |                                              |                                                                                |
| <b>Toll. s</b> inch. +/-0,002<br>mm +/-0,05 |                                              |                                                                                |
| <b>Weight Kg/1000</b> 2.42                  |                                              |                                                                                |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350