

## SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:  
Oil dipped

Example of designation: HS-37



d1=shaft diameter  
d2=groove diameter  
d3=internal ring diameter  
s=thickness

HS - for shafts  
(in inches)



| description | Price<br>Euro x100 | % Price Change | Package |
|-------------|--------------------|----------------|---------|
| HS-134      | 68,00              | + 20%          | 100     |

| DESCRIPTION                          | GROOVE                                 | THRUST CAPACITY                                                                |
|--------------------------------------|----------------------------------------|--------------------------------------------------------------------------------|
| HS-134                               | d2 inch. 1.309<br>mm 33.25             | groove yield Newtons 7.179<br>L.B.S. 1,614                                     |
| d1 mm 34.11                          | Toll. d2 inch. +/-0,004<br>mm +/- 0,10 | (based on a groove material yield strength of 310/mm and a safety factor of 2) |
| d1 inch 1.343                        | c inch. 0.155<br>mm 3.94               |                                                                                |
|                                      | Toll. c inch. +0,004<br>mm +0,100      |                                                                                |
| RING IN THE UNSTRESSED STATE         |                                        |                                                                                |
| d3 inch. 1.282<br>mm 32.56           |                                        |                                                                                |
| Toll. d3 inch. -0,02<br>mm -0,51     |                                        |                                                                                |
| b inch. 0.034<br>mm 0.86             |                                        |                                                                                |
| Toll. b inch. +/-0,002<br>mm +/-0,05 |                                        |                                                                                |
| s inch. 0.150<br>mm 3.81             |                                        |                                                                                |
| Toll. s inch. +/-0,004<br>mm +/-0,10 |                                        |                                                                                |
| Weight Kg/1000 2.69                  |                                        |                                                                                |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350