


SMALLEY® SPIRAL RETAINING RINGS
SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped

Example of designation: FSE-0050


d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Heavy duty series
FSE - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
FSE-0112	96,00	+ 20%	-	500

DESCRIPTION	GROOVE	THRUST CAPACITY
FSE-0112	d2 inch. 1.077 mm 27.36	ring shear Newtons 33.872 L.B.S. 7,615
d1 mm 28.58	Toll. d2 inch. -0,008 mm -0,200	(safety factor =3)
d1 inch 1.125	c inch. 0.063 mm 1.60	groove yield Newtons 8.491 L.B.S. 1,909
RING IN THE UNSTRESSED STATE		(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 1.069 mm 27.15	Toll. c inch. +0,006 mm +0,150	
Toll. d3 inch. -0,015 mm -0,38		
b inch. 0.128 mm 3.25		
Toll. b inch. +0,003/-0,005 mm +0,08/-0,13		
s inch. 0.057 mm 1.45		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 3.18		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350