


SMALLEY® SPIRAL RETAINING RINGS

SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped

Example of designation: FHE-0050



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Heavy duty
series
FHE - for bores
(in inches)



description	Price Euro x100	% Price Change	Package
FHE-0300	250,00	+ 20%	100

DESCRIPTION	GROOVE	THRUST CAPACITY
FHE-0300	d2 inch. 3.118 mm 79.20	ring shear Newtons 136.589 L.B.S. 30,708 (safety factor =3)
d1 mm 76.20	Toll. d2 inch. +0,012 mm +0,300	groove yield Newtons 55.649 L.B.S. 12,511 (based on a groove material yield strength of 310/mm and a safety factor of 2)
d1 inch 3.000	c inch. 0.104 mm 2.64	
	Toll. c inch. +0,006 mm +0,150	
RING IN THE UNSTRESSED STATE		
d3 inch. 3.145 mm 79.88		
Toll. d3 inch. +0,030 mm +0,76		
b inch. 0.200 mm 5.08		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.095 mm 2.41		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 19.95		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350