


**SMALLEY® SPIRAL RETAINING RINGS**
**SAE 1070-90 Carbon Steel**

surface treatment:  
**Oil dipped**
**Example of designation: XAS 31**

**d1**=shaft diameter  
**d2**=groove diameter  
**d3**=internal ring diameter  
**S**=thickness

Medium duty  
series  
**XAS - for shafts**  
(in inches)


| description    | Price<br>Euro x100 | % Price Change |   | Package |
|----------------|--------------------|----------------|---|---------|
|                |                    | 1              | 2 |         |
| <b>XAS-206</b> | <b>170,00</b>      | + 20%          | - | 100     |

| DESCRIPTION                                 | GROOVE                                       | THRUST CAPACITY                                                                      |
|---------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------------------|
| XAS-206                                     | <b>d2</b> inch. 1.966<br>mm 49.94            | <b>ring shear</b> Newtons 77.798<br>L.B.S. 17,491                                    |
| <b>d1 mm</b> 52.37                          | <b>Toll. d2</b> inch. +/-0,006<br>mm +/-0,15 | (safety factor =3)                                                                   |
| <b>d1 inch</b> 2.062                        | <b>c</b> inch. 0.086<br>mm 2.18              | <b>groove yield</b> Newtons 31.119<br>L.B.S. 6,996                                   |
| <b>RING IN THE UNSTRESSED STATE</b>         | <b>Toll. c</b> inch. +0,005<br>mm +0,130     | (based on a groove material yield<br>strength of 310/mm and a safety factor<br>of 2) |
| <b>d3</b> inch. 1.936<br>mm 49.17           |                                              |                                                                                      |
| <b>Toll. d3</b> inch. -0,046<br>mm -1,17    |                                              |                                                                                      |
| <b>b</b> inch. 0.156<br>mm 3.96             |                                              |                                                                                      |
| <b>Toll. b</b> inch. +/-0,005<br>mm +/-0,13 |                                              |                                                                                      |
| <b>s</b> inch. 0.078<br>mm 1.98             |                                              |                                                                                      |
| <b>Toll. s</b> inch. +/-0,002<br>mm +/-0,05 |                                              |                                                                                      |
| <b>Weight Kg/1000</b> 10.16                 |                                              |                                                                                      |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350