


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XAS 31

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Medium duty
series
XAS - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
XAS-255	270,00	+ 20%	-	100

DESCRIPTION	GROOVE	THRUST CAPACITY
XAS-255	d2 inch. 2.443 mm 62.05	ring shear Newtons 96.549 L.B.S. 21,706
d1 mm 65.00	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 2.559	c inch. 0.086 mm 2.18	groove yield Newtons 46.665 L.B.S. 10,491
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 2.413 mm 61.29		
Toll. d3 inch. -0,046 mm -1,17		
b inch. 0.187 mm 4.75		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.078 mm 1.98		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 15.17		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350