


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XAS 31

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Medium duty
series
XAS - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
XAS-125	47,00	+ 20%	-	500

DESCRIPTION	GROOVE	THRUST CAPACITY
XAS-125	d2 inch. 1.194 mm 30.33	ring shear Newtons 32.838 L.B.S. 7,383
d1 mm 31.75	Toll. d2 inch. +/-0,004 mm +/-0,1	(safety factor =3)
d1 inch 1.250	c inch. 0.056 mm 1.42	groove yield Newtons 11.004 L.B.S. 2,474
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,004 mm +0,100	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 1.179 mm 29.95		
Toll. d3 inch. -0,031 mm -0,79		
b inch. 0.093 mm 2.36		
Toll. b inch. +/-0,003 mm +/-0,08		
s inch. 0.050 mm 1.27		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 2.36		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350