


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: XAS 31



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Medium duty
series
**XAS - for shafts
(in inches)**



description	Price Euro x100	% Price Change		Package
		1	2	
XAS-143	55,00	+ 20%	-	250

DESCRIPTION	GROOVE	THRUST CAPACITY
XAS-143	d2 inch. 1.370 mm 34.80	ring shear Newtons 37.777 L.B.S. 8,493
d1 mm 36.53	Toll. d2 inch. +/-0,004 mm +/-0,1	(safety factor =3)
d1 inch 1.438	c inch. 0.056 mm 1.42	groove yield Newtons 15.372 L.B.S. 3,456
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,004 mm +0,100	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 1.351 mm 34.32		
Toll. d3 inch. -0,031 mm -0,79		
b inch. 0.109 mm 2.77		
Toll. b inch. +/-0,003 mm +/-0,08		
s inch. 0.050 mm 1.27		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 3.18		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350