


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XDS-50

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Light duty series
XDS - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
XDS-50	39,00	+ 20%	-	1000

DESCRIPTION	GROOVE	THRUST CAPACITY
XDS-50	d2 inch. 0.474 mm 12.04	ring shear Newtons 9.223 L.B.S. 2,073
d1 mm 12.70	Toll. d2 inch. +/-0,002 mm +/-0,05	(safety factor =3)
d1 inch 0.500	c inch. 0.039 mm 0.99	groove yield Newtons 2.044 L.B.S. 459
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,003 mm +0,080	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 0.465 mm 11.81		
Toll. d3 inch. -0,025 mm -0,64		
b inch. 0.048 mm 1.22		
Toll. b inch. +/-0,003 mm +/-0,08		
s inch. 0.035 mm 0.89		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 0.34		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350