


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XDH-112

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Light duty series
XDH - for bores
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
XDH-300	170,00	+ 20%	-	100

DESCRIPTION	GROOVE	THRUST CAPACITY
XDH-300	d2 inch. 3.124 mm 79.35	ring shear Newtons 93.988 L.B.S. 21,130
d1 mm 76.20	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 3.000	c inch. 0.068 mm 1.73	groove yield Newtons 58.480 L.B.S. 13,148
	Toll. c inch. +0,004 mm +0,100	(based on a groove material yield strength of 310/mm and a safety factor of 2)
RING IN THE UNSTRESSED STATE		
d3 inch. 3.154 mm 80.11		
Toll. d3 inch. +0,078 mm +1,98		
b inch. 0.187 mm 4.75		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.062 mm 1.57		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 14.06		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350