


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: XDH-112



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Light duty series
XDH - for bores
(in inches)



description	Price Euro x100	% Price Change		Package
		1	2	
XDH-375	260,00	+ 20%	-	50

DESCRIPTION	GROOVE	THRUST CAPACITY
XDH-375	d2 inch. 3.874 mm 98.40	ring shear Newtons 117.485 L.B.S. 26,413
d1 mm 95.25	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 3.750	c inch. 0.068 mm 1.73	groove yield Newtons 73.100 L.B.S. 16,434
RING IN THE UNSTRESSED STATE		(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 3.904 mm 99.16	Toll. c inch. +0,004 mm +0,100	
Toll. d3 inch. +0,078 mm +1,98		
b inch. 0.187 mm 4.75		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.062 mm 1.57		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 17.57		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350