


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: XDH-112

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Light duty series
XDH - for bores
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
XDH-600	700,00	+ 20%	-	25

DESCRIPTION	GROOVE	THRUST CAPACITY
XDH-600	d2 inch. 6.160 mm 156.46	ring shear Newtons 271.651 L.B.S. 61,073
d1 mm 152.40	Toll. d2 inch. +/-0,007 mm +/-0,18	(safety factor =3)
d1 inch 6.000	c inch. 0.103 mm 2.62	groove yield Newtons 150.917 L.B.S. 33,929
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 6.220 mm 157.99		
Toll. d3 inch. +0,125 mm +3,18		
b inch. 0.250 mm 6.35		
Toll. b inch. +/-0,005 mm +/-0,13		
s inch. 0.093 mm 2.36		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 56.59		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350