


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WSM-25



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Heavy duty
series
WSM - for shafts
(in inches)



description	Price Euro x100	% Price Change	Package
WSM-300	260,00	+ 20%	100

DESCRIPTION	GROOVE	THRUST CAPACITY
WSM-300	d2 inch. 2.838 mm 72.09	ring shear Newtons 155.947 L.B.S. 35,060 (safety factor =3)
d1 mm 76.20	Toll. d2 inch. +/-0,006 mm +/-0,15	groove yield Newtons 76.417 L.B.S. 17,180 (based on a groove material yield strength of 310/mm and a safety factor of 2)
d1 inch 3.000	c inch. 0.103 mm 2.62	
	Toll. c inch. +0,005 mm +0,130	
RING IN THE UNSTRESSED STATE		
d3 inch. 2.818 mm 71.58		
Toll. d3 inch. -0,03 mm -0,76		
b inch. 0.225 mm 5.72		
Toll. b inch. +0,004/-0,006 mm +0,10/-0,15		
s inch. 0.093 mm 2.36		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 24.18		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350