


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WSM-25



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Heavy duty
series
WSM - for shafts
(in inches)



description	Price Euro x100	% Price Change		Package
WSM-375	450,00	1 + 20%	2 -	50

DESCRIPTION	GROOVE	THRUST CAPACITY
WSM-375	d2 inch. 3.552 mm 90.22	ring shear Newtons 232.675 L.B.S. 52,310 (safety factor =3)
d1 mm 95.25	Toll. d2 inch. +/-0,006 mm +/-0,15	groove yield Newtons 116.716 L.B.S. 26,240 (based on a groove material yield strength of 310/mm and a safety factor of 2)
d1 inch 3.750	c inch. 0.120 mm 3.05	
	Toll. c inch. +0,005 mm +0,130	
RING IN THE UNSTRESSED STATE		
d3 inch. 3.527 mm 89.59		
Toll. d3 inch. -0,035 mm -0,89		
b inch. 0.270 mm 6.86		
Toll. b inch. +0,004/-0,006 mm +0,10/-0,15		
s inch. 0.111 mm 2.82		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 43.59		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350