


SMALLEY® SPIRAL RETAINING RINGS

Stainless steel
AISI 302

surface treatment:
Steam degreasing
Ultrasonic cleaning

Example of designation:
WSM-25-S02



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Heavy duty
series
WSM - for shafts
(in inches)



description	Price Euro x100	% Price Change	Package
WSM-118-S02	126,00	+ 20%	500

DESCRIPTION	GROOVE	THRUST CAPACITY
WSM-118-S02	d2 inch. 1.118 mm 28.40	ring shear Newtons 34.872 L.B.S. 7,840
d1 mm 30.18	Toll. d2 inch. +/-0,004 mm +/-0,1	(safety factor =3)
d1 inch 1.188	c inch. 0.056 mm 1.42	groove yield Newtons 13.077 L.B.S. 2,940
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,004 mm +0,100	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 1.105 mm 28.07		
Toll. d3 inch. -0,013 mm -0,33		
b inch. 0.103 mm 2.62		
Toll. b inch. +0,003/-0,005 mm +008/-013		
s inch. 0.050 mm 1.27		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 2.31		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350