


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WST-46



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
s=thickness

Medium-heavy
duty series
WST - for shafts
(in inches)



description	Price Euro x100	% Price Change		Package
		1	2	
WST-250	190,00	+ 20%	-	100

DESCRIPTION	GROOVE	THRUST CAPACITY
WST-250	d2	ring shear
d1 mm	inch. 2.385 mm 60.58	Newtons 114.447 L.B.S. 25,730
d1 inch	Toll. d2	(safety factor =3)
	inch. +/-0,006 mm +/-0,15	groove yield
	c	Newtons 45.592 L.B.S. 10,250
	Toll. c	(based on a groove material yield strength of 310/mm and a safety factor of 2)
	inch. +0,005 mm +0,130	
RING IN THE UNSTRESSED STATE		
d3	inch. 2.366 mm 60.10	
Toll. d3	inch. -0,025 mm -0,64	
b	inch. 0.188 mm 4.78	
Toll. b	inch. +/-0,005 mm +/-0,13	
s	inch. 0.078 mm 1.98	
Toll. s	inch. +/-0,003 mm +/-0,08	
Weight Kg/1000	14.33	

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350