


SMALLEY® SPIRAL RETAINING RINGS
SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped
Example of designation: WH-50

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Medium duty series
WH - for bores (in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
WH-51	20,00	+ 20%	-	1000

DESCRIPTION	GROOVE	THRUST CAPACITY
WH-51	d2 inch. 0.538 mm 13.67	ring shear Newtons 9.118 L.B.S. 2,050
d1 mm 13.00	Toll. d2 inch. +/-0,002 mm +/-0,05	(safety factor =3)
d1 inch 0.512	c inch. 0.030 mm 0.76	groove yield Newtons 2.091 L.B.S. 470
	Toll. c inch. +0,003 mm +0,080	(based on a groove material yield strength of 310/mm and a safety factor of 2)
RING IN THE UNSTRESSED STATE		
d3 inch. 0.544 mm 13.82		
Toll. d3 inch. +0,013 mm +0,33		
b inch. 0.045 mm 1.14		
Toll. b inch. +0,003/-0,005 mm +0,08/-0,13		
s inch. 0.025 mm 0.64		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 0.22		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350