


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WHM-25



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
s=thickness

Heavy duty series
WHM - for bores
(in inches)



description	Price Euro x100	% Price Change		Package
WHM-250	140,00	1	2	100
		+ 20%	-	

DESCRIPTION	GROOVE	THRUST CAPACITY
WHM-250	d2	ring shear
d1 mm 63.50	inch. 2.648 mm 67.26	Newtons 114.447 L.B.S. 25,730
d1 inch 2.500	Toll. d2	(safety factor =3)
	inch. +/-0,006 mm +/-0,15	groove yield
	c	Newtons 58.180 L.B.S. 13,080
	inch. 0.086 mm 2.18	(based on a groove material yield strength of 310/mm and a safety factor of 2)
	Toll. c	
	inch. +0,005 mm +0,130	
RING IN THE UNSTRESSED STATE		
d3	inch. 2.667 mm 67.74	
Toll. d3	inch. +0,025 mm +0,64	
b	inch. 0.200 mm 5.08	
Toll. b	inch. +0,004/-0,006 mm +0,10/-0,15	
s	inch. 0.078 mm 1.98	
Toll. s	inch. +/-0,003 mm +/-0,08	
Weight Kg/1000	15.12	

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350