


SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: WHM-25



Heavy duty series
WHM - for bores
(in inches)



description	Price Euro x100	% Price Change		Package
WHM-256	180,00	1 + 20%	2 -	100

DESCRIPTION	GROOVE	THRUST CAPACITY
WHM-256	d2 inch. 2.714 mm 68.94	ring shear Newtons 133.173 L.B.S. 29,940
d1 mm 65.07	Toll. d2 inch. +/-0,006 mm +/-0,15	(safety factor =3)
d1 inch 2.562	c inch. 0.103 mm 2.62	groove yield Newtons 61.204 L.B.S. 13,760
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,005 mm +0,130	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 2.733 mm 69.42		
Toll. d3 inch. +0,030 mm +0,76		
b inch. 0.225 mm 5.72		
Toll. b inch. +0,004/-0,006 mm +0,10/-0,15		
s inch. 0.093 mm 2.36		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 20.89		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350