


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: WHT-50

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Medium-heavy
duty series
**WHT - for bores
(in inches)**


description	Price Euro x100	% Price Change		Package
		1	2	
WHT-156	51,00	+ 20%	-	250

DESCRIPTION	GROOVE	THRUST CAPACITY
WHT-156	d2 inch. 1.647 mm 41.83	ring shear Newtons 56.845 L.B.S. 12,780
d1 mm 39.67	Toll. d2 inch. +/-0,005 mm +/-0,13	(safety factor =3)
d1 inch 1.562	c inch. 0.068 mm 1.73	groove yield Newtons 21.128 L.B.S. 4,750
	Toll. c inch. +0,004 mm +0,100	(based on a groove material yield strength of 310/mm and a safety factor of 2)
RING IN THE UNSTRESSED STATE		
d3 inch. 1.659 mm 42.14		
Toll. d3 inch. +0,020 mm +0,51		
b inch. 0.113 mm 2.87		
Toll. b inch. +/-0,004 mm +/-0,1		
s inch. 0.062 mm 1.57		
Toll. s inch. +/-0,003 mm +/-0,08		
Weight Kg/1000 4.20		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350