


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped
Example of designation: VH-25

Light duty series
**VH - for bores
(in inches)**

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

description	Price Euro x100	% Price Change		Package
		1	2	
VH-112	16,40	+ 20%	-	500

DESCRIPTION		GROOVE		THRUST CAPACITY	
VH-112		d2		ring shear	
d1 mm	28.58	inch. 1.169 mm 29.69		Newtons 16.502 L.B.S. 3,710	
d1 inch	1.125	Toll. d2		(safety factor =3)	
		inch. +/-0,004 mm +/-0,1		groove yield	
		c		Newtons 7.784 L.B.S. 1,750	
		inch. 0.031 mm 0.79		(based on a groove material yield strength of 310/mm and a safety factor of 2)	
		Toll. c			
		inch. +0,002 mm +0,050			
RING IN THE UNSTRESSED STATE					
d3	inch. 1.180 mm 29.97				
Toll. d3	inch. +0,015 mm +0,38				
b	inch. 0.088 mm 2.24				
Toll. b	inch. +/-0,004 mm +/-0,1				
s	inch. 0.025 mm 0.64				
Toll. s	inch. +/-0,0015 mm +/-0,04				
Weight Kg/1000	0.90				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350