


SMALLEY® SPIRAL RETAINING RINGS

Stainless steel
AISI 302

surface treatment:
Steam degreasing
Ultrasonic cleaning

Example of designation:
VH-25-S02



Light duty series
VH - for bores
(in inches)



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

description	Price Euro x100	% Price Change		Package
		1	2	
VH-31-S02	29,00	+ 20%	-	1000

DESCRIPTION	GROOVE	THRUST CAPACITY
VH-31-S02	d2 inch. 0.326 mm 8.28	ring shear Newtons 3.336 L.B.S. 750
d1 mm 7.92	Toll. d2 inch. +/-0,002 mm +/-0,05	(safety factor =3)
d1 inch 0.312	c inch. 0.018 mm 0.46	groove yield Newtons 685 L.B.S. 154
RING IN THE UNSTRESSED STATE	Toll. c inch. +0,002 mm +0,050	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d3 inch. 0.329 mm 8.36		
Toll. d3 inch. +0,010 mm +0,25		
b inch. 0.025 mm 0.64		
Toll. b inch. +/-0,004 mm +/-0,1		
s inch. 0.015 mm 0.38		
Toll. s inch. +/-0,0015 mm +/-0,04		
Weight Kg/1000 0.05		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350