


## SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:  
Oil dipped

Example of designation: HHMU-10



HHMU - for  
bores without  
removing ear



d1=shaft diameter  
d2=groove diameter  
d3=internal ring diameter  
S=thickness

| description | Price<br>Euro x100 | % Price Change |        | Package |
|-------------|--------------------|----------------|--------|---------|
| HHMU-20     | 43,00              | 1<br>+ 20%     | 2<br>- | 500     |

| DESCRIPTION                         | GROOVE     | THRUST CAPACITY                                                                                                     |
|-------------------------------------|------------|---------------------------------------------------------------------------------------------------------------------|
| HHMU-20                             | d2         | <b>groove yield</b> Newtons 2.971<br>(based on a groove material yield strength of 310/mm and a safety factor of 2) |
| d1 mm      20.00                    | mm 20.61   |                                                                                                                     |
|                                     | Toll. d2   |                                                                                                                     |
|                                     | mm +/-0,08 |                                                                                                                     |
|                                     | c          |                                                                                                                     |
|                                     | mm 2.36    |                                                                                                                     |
|                                     | Toll. c    |                                                                                                                     |
|                                     | mm +0,080  |                                                                                                                     |
| <b>RING IN THE UNSTRESSED STATE</b> |            |                                                                                                                     |
| d3                                  | mm 21.01   |                                                                                                                     |
| Toll. d3                            | mm +0,46   |                                                                                                                     |
| b                                   | mm 0.61    |                                                                                                                     |
| Toll. b                             | mm +/-0,04 |                                                                                                                     |
| s                                   | mm 2.24    |                                                                                                                     |
| Toll. s                             | mm +/-0,10 |                                                                                                                     |
| Weight Kg/1000                      | 0.74       |                                                                                                                     |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350