


SMALLEY® SPIRAL RETAINING RINGS
SAE 1070-90 Carbon Steel

 surface treatment:
Oil dipped
Example of designation: HHMU-10

HHMU - for bores without removing ear

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

description	Price Euro x100	% Price Change		Package
		1	2	
HHMU-72	320,00	+ 20%	-	50

DESCRIPTION	GROOVE	THRUST CAPACITY
HHMU-72	d2	groove yield Newtons 20.054 (based on a groove material yield strength of 310/mm and a safety factor of 2)
d1 mm 72.00	Toll. d2 mm 73.14	
RING IN THE UNSTRESSED STATE	c mm 5.87	
d3 mm 74.58	Toll. c mm +0,130	
Toll. d3 mm +0,76		
b mm 1.14		
Toll. b mm +/-0,05		
s mm 5.72		
Toll. s mm +/-0,13		
Weight Kg/1000 12.22		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
 Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL
 viale Pier Paolo Pasolini, 83
 Sesto San Giovanni Mi - Italy

Sales department
 250@gandini.it
 tel +39 02 241 047 250

Administration
 350@gandini.it
 tel +39 02 241 047 350