

SMALLEY® SPIRAL RETAINING RINGS

SAE 1070-90 Carbon Steel

surface treatment:
Oil dipped

Example of designation: HHU-37



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

HHU for bores
(in inches)
without
removing ear



description	Price Euro x100	% Price Change	Package
HHU-112	50,00	+ 20%	250

DESCRIPTION	GROOVE	THRUST CAPACITY
HHU-112	d2 inch. 1.155 mm 29.34	groove yield Newtons 5.306 L.B.S. 1,193
d1 mm 28.58	Toll. d2 inch. +/-0,004 mm +/- 0,10	(based on a groove material yield strength of 310/mm and a safety factor of 2)
d1 inch 1.125	c inch. 0.123 mm 3.12	
	Toll. c inch. +0,004 mm +0,100	
RING IN THE UNSTRESSED STATE		
d3 inch. 1.178 mm 29.92		
Toll. d3 inch. +0,020 mm +0,51		
b inch. 0.030 mm 0.76		
Toll. b inch. +/-0,002 mm +/-0,05		
s inch. 0.118 mm 3.00		
Toll. s inch. +/-0,004 mm +/-0,10		
Weight Kg/1000 1.65		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350