

SMALLEY® SPIRAL RETAINING RINGS
SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped
Example of designation: FSE-0050

d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Heavy duty series
FSE - for shafts
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
FSE-0187	105,00	+ 20%	-	250

DESCRIPTION		GROOVE		THRUST CAPACITY	
FSE-0187		d2	inch. 1.783 mm 45.29	ring shear	Newtons 66.208 L.B.S. 14,885
d1 mm	47.63	Toll. d2	inch. -0,01 mm -0,250	(safety factor =3)	
d1 inch	1.875	c	inch. 0.073 mm 1.85	groove yield	Newtons 27.119 L.B.S. 6,097
RING IN THE UNSTRESSED STATE		Toll. c	inch. +0,006 mm +0,150	(based on a groove material yield strength of 310/mm and a safety factor of 2)	
d3	inch. 1.767 mm 44.88				
Toll. d3	inch. -0,02 mm -0,51				
b	inch. 0.158 mm 4.01				
Toll. b	inch. +0,003/-0,005 mm +0,08/-0,13				
s	inch. 0.067 mm 1.70				
Toll. s	inch. +/-0,002 mm +/-0,05				
Weight Kg/1000	7.74				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350