


SMALLEY® SPIRAL RETAINING RINGS

SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped

Example of designation: FSE-0050



d1=shaft diameter
d2=groove diameter
d3=internal ring diameter
S=thickness

Heavy duty
series
FSE - for shafts
(in inches)



description	Price Euro x100	% Price Change	Package
FSE-0156	99,00	+ 20%	250

DESCRIPTION	GROOVE	THRUST CAPACITY
FSE-0156	d2	ring shear
d1 mm 39.67	inch. 1.470	Newton's 55.155
d1 inch 1.562	mm 37.34	L.B.S. 12,400
	Toll. d2	(safety factor =3)
	inch. -0,01	
	mm -0,250	
	c	groove yield
	inch. 0.073	Newton's 22.591
	mm 1.85	L.B.S. 5,079
	Toll. c	(based on a groove material yield strength of 310/mm and a safety factor of 2)
	inch. +0,006	
	mm +0,150	
RING IN THE UNSTRESSED STATE		
d3	inch. 1.457	
	mm 37.01	
Toll. d3	inch. -0,02	
	mm -0,51	
b	inch. 0.158	
	mm 4.01	
Toll. b	inch. +0,003/-0,005	
	mm +0,08/-0,13	
s	inch. 0.067	
	mm 1.70	
Toll. s	inch. +/-0,002	
	mm +/-0,05	
Weight Kg/1000	6.45	

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350