


SMALLEY® SPIRAL RETAINING RINGS

SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped

Example of designation: FHE-0050



d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Heavy duty
series
FHE - for bores
(in inches)



description	Price Euro x100	% Price Change	Package
FHE-0075	30,00	+ 20%	1000

DESCRIPTION	GROOVE	THRUST CAPACITY
FHE-0075	d2 inch. 0.790 mm 20.07	ring shear Newtons 15.510 L.B.S. 3,487
d1 mm 19.05	Toll. d2 inch. +0,005 mm +0,130	(safety factor =3)
d1 inch 0.750	c inch. 0.043 mm 1.09	groove yield Newtons 4.715 L.B.S. 1,060
	Toll. c inch. +0,006 mm +0,150	(based on a groove material yield strength of 310/mm and a safety factor of 2)
RING IN THE UNSTRESSED STATE		
d3 inch. 0.797 mm 20.24		
Toll. d3 inch. +0,013 mm +0,33		
b inch. 0.075 mm 1.91		
Toll. b inch. +/-0,004 mm +/-0,10		
s inch. 0.037 mm 0.94		
Toll. s inch. +/-0,002 mm +/-0,05		
Weight Kg/1000 0.66		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350