


SMALLEY® SPIRAL RETAINING RINGS
SAE 1060-75 Carbon Steel

surface treatment:
Oil dipped
Example of designation: FHE-0050

d1=shaft diameter
d2=groove diameter
d3=external ring diameter
S=thickness

Heavy duty
series
FHE - for bores
(in inches)


description	Price Euro x100	% Price Change		Package
		1	2	
FHE-0331	330,00	+ 20%	-	50

DESCRIPTION		GROOVE		THRUST CAPACITY	
FHE-0331		d2	inch. 3.450 mm 87.63	ring shear	Newtons 173.258 L.B.S. 38,952
d1 mm	84.12	Toll. d2	inch. +0,013 mm +0,330	(safety factor =3)	
d1 inch	3.312	c	inch. 0.124 mm 3.15	groove yield	Newtons 71.853 L.B.S. 16,154
RING IN THE UNSTRESSED STATE		Toll. c	inch. +0,007 mm +0,180	(based on a groove material yield strength of 310/mm and a safety factor of 2)	
d3	inch. 3.483 mm 88.47				
Toll. d3	inch. +0,035 mm +0,89				
b	inch. 0.248 mm 6.30				
Toll. b	inch. +/-0,005 mm +/-0,13				
s	inch. 0.115 mm 2.92				
Toll. s	inch. +/-0,003 mm +/-0,08				
Weight Kg/1000	33.17				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350