


SMALLEY® SPIRAL RETAINING RINGS

**Acciaio al Carbonio per Molle
SAE 1070-90**

surface treatment:
Oliatura

Esempio di designazione: ES-6



d1=diametro albero
d2=diametro gola
d3=diametro interno anello
S=spessore

Medium duty
series
ES - per alberi



description	Price Euro x100	% Price Change		Package
ES-250	1.400,00	1 + 20%	2 -	25

DESCRIPTION	GROOVE	THRUST CAPACITY
ES-250	d2	ring shear Newtons 495.470 (safety factor =3)
d1 mm 250.00	mm 243.80	
	Toll. d2	groove yield Newtons 377.440 (based on a groove material yield strength of 310/mm and a safety factor of 2)
	mm +/-0,200	
RING IN THE UNSTRESSED STATE	c	
d3	mm 2.40	
mm 241.83	Toll. c	
Toll. d3	mm +0,150	
mm -10,78		
b		
mm 9.53		
Toll. b		
mm +.10/-0,21		
s		
mm 2.18		
Toll. s		
mm +/-0,10		
Weight Kg/1000		
124.00		

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350