

RETAINING RINGS

Material: Spring steel


Hardness:
45÷50 HRC450÷520 HV

SURFACE FINISHES
Phosphated and oiled
Blackened and oiled
Manufacturer's choice

On request: inox steel

Example of designation:
ring type **ZJ 30**

non in tensione
unstressed



self-locking
type **ZJ** - for
bores



d₁=bore diameter
d₂=groove diameter
d₃=external diameter in the unstressed state
d₄=inner diameter in the unstressed state
s=thickness

d1	Description	Price euro /100	% Price Change	Package
35.00	ZJ 35	25,00	-	500

RING		GROOVE		SUPPLEMENTARY DATA	
d₁	35.00	d₂	35.2	n	2.0
s	0.50	tole d₂	0.130	tabs	12
d₃	35.40	m	1.0	H (N) retaining force of self-locking	900
d₄	25.0			X	4.0
weight kg/1000	1.320				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350