GANDINI

Sunday, May 19, 2024

RETAINING RINGS

Material:Spring steel

Hardness:

SURFACE FINISHES
Phosphated and oiled
Blackened and oiled
Manufacturer's choice

Example of designation:
ring type **JK 25**



DIN 984 Type **JK**
JK for bores

d_1=bore diameter
d_2=grove diameter
d_3=ring diameter in the unstressed state
s=thickness

d1	Description	Price euro /100	% Price Change 1	% Price Change 2	Package
34.00	**JK 34**	**25,00**	-	-	250

RING	
d_1	34.00
s	1.50
tole s	-0.06
d_3	36.5
tole d_3	+0.50 -0.25
a max	5.3
b ~	3.4
d_5 min	2.5
weight kg/1000	3.800

GROOVE	
d_2	35.7
tole d_2	0.25
m	1.60
t	0.85

SUPPLEMENTARY DATA	
n	2.5
FN (kN)	15.4
FR (kN)	26.2
g	1.5
FRg (kN)	6.3
AN (mm2)	62.6
K (kN.mm)	50.0
tabs	6
plier	ZGJ 2

Technical informations are indicative and can be updated.
Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements and mechanical parts machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350