

## RETAINING RINGS


**Material:** Spring steel

**Hardness:**

**SURFACE FINISHES**  
**Phosphated and oiled**  
**Blackened and oiled**  
 Manufacturer's choice

**Example of designation:**  
**NA 125 (1-1/4)**

non in tensione  
unstressed



Inch type **NA**  
 DIN 471  
 UNI 3653-7435  
 for shafts



**d1**=shaft diameter  
**d2**=groove diameter  
**d3**=ring diameter in the unstressed state  
**s**=thickness

| s     | Description  | Price<br>euro /100 | % Price Change |   | Package |
|-------|--------------|--------------------|----------------|---|---------|
|       |              |                    | 1              | 2 |         |
| 0.025 | NA 31 (5/16) | 7,80               | -              | - | 2000    |

| RING    |       | GROOVE | SUPPLEMENTARY DATA |       |
|---------|-------|--------|--------------------|-------|
| d1      | 7.90  | d2     | 0.290              | plier |
| d1 inch | 0.312 |        |                    | ZGA 0 |
| s       | 0.025 |        |                    |       |
| d3      | 0.281 |        |                    |       |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
 Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
 of fasteners, fixing elements  
 and mechanical parts  
 machining

**GANDINI FASTENERS SRL**  
 viale Pier Paolo Pasolini, 83  
 Sesto San Giovanni Mi - Italy

**Sales department**  
 250@gandini.it  
 tel +39 02 241 047 250

**Administration**  
 350@gandini.it  
 tel +39 02 241 047 350