

RETAINING RINGS

Material: Spring steel

Hardness:

SURFACE FINISHES
Phosphated and oiled
Blackened and oiled
 Manufacturer's choice

Example of designation:
 ring type J 30



DIN 472
 UNI 3654-7437
 Type J - for
 bores



d₁=bore diameter
 d₂=groove diameter
 d₃=ring diameter in the unstressed state
 s=thickness

d1	Description	Price euro /100	Variazione Prezzo %		Confezione
1	2				
272,00	(J 272)	-	-	-	25

RING		GROOVE		SUPPLEMENTARY DATA	
d ₁	272,00	d ₂	280,0	n	12,0
s	5,00	tole d ₂	0,81	FN (kN)	577,00
tole s	-0,12	m	5,15	FR (kN)	515,0
d ₃	285,0	t	4,00	g	4,0
tole d ₃	+2.00 -0.81			FRg (kN)	76,5
a max	16,2			AN (mm ²)	3.465,0
b ~	16,0			K (kN.mm)	1.180,0
d ₅ min	5,0			plier	ZGJ 5-6
weight kg/1000	388,000				

I dati riportati sono indicativi e possono essere in qualsiasi momento variati dai produttori.

Copyright Gandini Fasteners S.r.l. Tutti i diritti sono riservati. Ogni riproduzione, anche parziale, è vietata senza espressa autorizzazione della Gandini Fasteners S.r.l.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano - Italy
 Tel. +39 02 241 047 250 Fax +39 02 241 047 74 - 250@gandini.it

Production and distribution
 of fasteners, fixing elements
 and mechanical parts
 machining

GANDINI FASTENERS SRL
 viale Pier Paolo Pasolini, 83
 Sesto San Giovanni Mi - Italy

Sales department
 250@gandini.it
 tel +39 02 241 047 250

Administration
 350@gandini.it
 tel +39 02 241 047 350