

## RETAINING RINGS

**Material:** Spring steel


**Hardness::**  
HRC 44-49

**Diameter tolerances:**  
**D=** ISO d12  
**d=** ISO D12

**SURFACE FINISHES**  
**Phosphated and oiled**  
**Only oiled**  
Manufacturer's choice

**On request: special diameter and special thickness**

**Example of designation:**  
washer type **SS 40x50**



**d=** inner diameter  
**D=** external diameter  
**s=** thickness

Support  
washers type  
**SS - DIN 988**



| d     | Description | Price<br>euro /100 | % Price Change |   | Package |
|-------|-------------|--------------------|----------------|---|---------|
|       |             |                    | 1              | 2 |         |
| 16.00 | SS 16X 22   | 14,00              | -              | - | 1000    |

| RING           |       |
|----------------|-------|
| D              | 22.00 |
| d              | 16.00 |
| s              | 1.5   |
| tole s         | -0.05 |
| weight kg/1000 | 2.100 |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350