

RETAINING RINGS


Material: Spring steel

Hardness:
45÷50 HRC 450÷520 HV

SURFACE FINISHES
Phosphated and oiled
Blackened and oiled
Manufacturer's choice

Example of designation:
ring type **SP 30**

Outer edges sharp or rounded, to manufacturer's choice



DIN 5417
circlips for
bearing type
SP - for shafts



d₁=shaft diameter
d₂=groove diameter
d₃=inner diameter in the unstressed state
s=thickness

d1	Description	Price euro /100	% Price Change		Package
			1	2	
80.00	SP 80	90,00	-	-	100

RING		GROOVE		SUPPLEMENTARY DATA	
d1	80.00	d2	76.81	FN (kN)	65.7
s	1.70	tole d2	-0.50	FR (kN)	34.8
tole s	-0.1	m	1.90	g	3.0
d3	75.4	Delta tole di m (solo x S)	0.3	FRg (kN)	5.25
tole d3	0.8			K (kN.mm)	64.0
e	5			n _{abl} .x1000 (giri/min)	3.000
r	0.6				
b ~	4.85				
tole b	-0.15				
d4	86.6				
weight kg/1000	16.300				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350