

## RETAINING RINGS


**Material:** Spring steel

**Hardness:**  
45÷50 HRC 450÷520 HV

**SURFACE FINISHES**  
**Phosphated and oiled**  
**Blackened and oiled**  
Manufacturer's choice

**Example of designation:**  
ring type **SP 30**

**Outer edges sharp or rounded, to manufacturer's choice**



DIN 5417  
circlips for  
bearing type  
**SP** - for shafts



**d<sub>1</sub>**=shaft diameter  
**d<sub>2</sub>**=groove diameter  
**d<sub>3</sub>**=inner diameter in the unstressed state  
**s**=thickness

| d1    | Description | Price<br>euro /100 | % Price Change |   | Package |
|-------|-------------|--------------------|----------------|---|---------|
|       |             |                    | 1              | 2 |         |
| 68.00 | SP 68       | 70,00              | -              | - | 100     |

| RING           |        | GROOVE                     |       | SUPPLEMENTARY DATA                 |       |
|----------------|--------|----------------------------|-------|------------------------------------|-------|
| d1             | 68.00  | d2                         | 64.82 | FN (kN)                            | 55.5  |
| s              | 1.70   | tole d2                    | -0.50 | FR (kN)                            | 43.0  |
| tole s         | -0.1   | m                          | 1.90  | g                                  | 2.5   |
| d3             | 63.4   | Delta tole di m (solo x S) | 0.3   | FRg (kN)                           | 7.30  |
| tole d3        | 0.8    |                            |       | K (kN.mm)                          | 75.0  |
| e              | 5      |                            |       | n <sub>abl</sub> .x1000 (giri/min) | 4.000 |
| r              | 0.6    |                            |       |                                    |       |
| b ~            | 4.85   |                            |       |                                    |       |
| tole b         | -0.15  |                            |       |                                    |       |
| d4             | 74.6   |                            |       |                                    |       |
| weight kg/1000 | 12.600 |                            |       |                                    |       |

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

**GANDINI FASTENERS SRL** viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy  
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution  
of fasteners, fixing elements  
and mechanical parts  
machining

**GANDINI FASTENERS SRL**  
viale Pier Paolo Pasolini, 83  
Sesto San Giovanni Mi - Italy

**Sales department**  
250@gandini.it  
tel +39 02 241 047 250

**Administration**  
350@gandini.it  
tel +39 02 241 047 350