

RETAINING RINGS

Material:
Spring steel

Hardness:
minimun 40 HRC


SURFACE FINISHES
Phosphated and oiled
Blackened and oiled
Manufacturer's choice

Example of designation:
ring type **SW 30**

non in tensione
unstressed

$d_1 \leq 38 \text{ mm}$

$d_1 \geq 40 \text{ mm}$



DIN 9927
circlips type
SW - for shafts



d_1 =shaft diameter
 d_2 =groove diameter
 d_3 =inner diameter in the unstressed state
 s =thickness

d1	Description	Price euro /100	% Price Change		Package
			1	2	
180.00	SW 180	240,00	-	-	25

RING		GROOVE		SUPPLEMENTARY DATA	
d_1	180.00	d_2	177.0	FN (kN)	140.00
s	3.0	tole d_2	-0.25	FR (kN)	67.50
d_3	175.2	m	3.2	$n_{abl} \cdot x1000$ (giri/min)	1.000
b ~	5.00				
weight kg/1000	61.200				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350