

RETAINING RINGS

Material:
Spring steel

Hardness:
minimun 40 HRC



SURFACE FINISHES
Phosphated and oiled
Blackened and oiled
Manufacturer's choice

Example of designation:
ring type **SW 30**

non in tensione
unstressed

$d_1 \leq 38 \text{ mm}$

$d_1 \geq 40 \text{ mm}$



DIN 9927
circlips type
SW - for shafts



d_1 =shaft diameter
 d_2 =groove diameter
 d_3 =inner diameter in the unstressed state
 s =thickness

d1	Description	Price euro /100	% Price Change	Package
7.00	SW 7	4,60	-	2000

RING		GROOVE		SUPPLEMENTARY DATA	
d_1	7.00	d_2	6.7	FN (kN)	0.54
s	0.7	tole d_2	-0.09	FR (kN)	3.50
d_3	6.5	m	0.8	$n_{abl} \times 1000$ (giri/min)	134.000
$b \sim$	1.20			plier	ZGS 0
weight kg/1000	0.120				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution
of fasteners, fixing elements
and mechanical parts
machining

GANDINI FASTENERS SRL
viale Pier Paolo Pasolini, 83
Sesto San Giovanni Mi - Italy

Sales department
250@gandini.it
tel +39 02 241 047 250

Administration
350@gandini.it
tel +39 02 241 047 350