RETAINING RINGS

Material: Spring steel

Hardness:

SURFACE FINISHES
Phosphated and oiled
Blackened and oiled
Manufacturer's choice

Example of designation:
ring type **AM 15 IMPILATI**



DIN 471
UNI 3653-7435
Type **AM** - for shafts-stacked

d_1=shafts diameter
d_2=grove diameter
d_3=ring diameter in the unstressed state
s=thickness

d1	Description	Price euro /100	% Price Change 1	% Price Change 2	Package
30.00	**AM 30 impilati**	**on demand**	-	-	-

RING	
d_1	30.00
s	1.50
tole s	-0.06
d_3	27.9
tole d_3	+0.21 -0.42
a max	5.0
b ~	3.5
d_5 min	2.0
weight kg/1000	3.320

GROOVE	
d_2	28.6
tole d_2	-0.21
m	1.60
t	0.70

SUPPLEMENTARY DATA	
n	2.1
FN (kN)	10.7
FR (kN)	32.10
g	1.5
FRg (kN)	7.65
AN (mm2)	64.0
K (kN.mm)	64.20
$n_{abl.}$x1000 (giri/min)	19.0
plier	ZGA 2

Technical informations are indicative and can be updated.
Copyright Gandini Fasteners S.r.l. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy
Tel. +39 02 241 047 250 Fax +39 02 241 047 74