

M3 4 NC 5 8 3 5

TECHNICAL PLASTIC AND METAL PARTS

MT 308-202 Acciaio Zincato

					Spacer SUB-D for connection <b>308 metal</b>
Code	Description	Price euro/1000	% Price Change	Package A	B C D E F gr

Colour	Colour number	
zinc	411 (XXX XXXX <b>XXX</b> XX)	
Colour description		zinc
Matches		zinc
Featured colours reserved.	Due to the screen, differences in colour may occur.	

212,00

+ 60%

100

Material	Material nr
Automat steel -	52 (XXX XXXX XXX <b>XX</b> )

## General informations:

308 2020 411 52

S300Pb. The type of steel is well-known and is used for distance pieces where a high mechanical strenght is required. There is a wide range of finishing possibilities, with standard zinc galvanizing or cadmium treatment being the most common.

Features		Chimical resistance		
feature	DIN	Resistance to	Valutation	
Relative density gr/cm <sup>3</sup>		Petrol	А	
Tensile strength MN/m <sup>2</sup>		Benzene	А	
Elongation at break % 7,5		Mineral oils	А	
Tensile modulus MN/m <sup>2</sup>		Vegetable oils	А	
Notched impact strength kJ/m <sup>2</sup>	2x10^5	Weak alkalis	А	
Ball indentation MN/m <sup>2</sup>		Strong alkalis	А	
Application temperature max °C	720x10^-7	Weak acids	В	
Volume resistivity cm		Strong acids	В	
Dissapation factor tan. 10 <sup>3</sup> Hz		A = good		
Dielectric strength MV/m Flammability UL94 > 1,6 mm		B = doubtful		
		<b>C</b> = poor		
Coefficient of friction (on steel)				
All data are indicative				

Technical informations are indicative and can be updated.

Copyright Gandini Fasteners S.r.I. All rights reserved. No part of this web site may be reproduced in any form without express permission.

GANDINI FASTENERS SRL viale Pier Paolo Pasolini, 83 - 20099 Sesto S.Giovanni Milano Italy Tel. +39 02 241 047 250 Fax +39 02 241 047 74

Production and distribution of fasteners, fixing elements viale Pier Paolo Pasolini, 83 and mechanical parts machining

**GANDINI FASTENERS SRL** Sesto San Giovanni Mi - Italy

Sales department 250@gandini.it tel +39 02 241 047 250 Administration 350@gandini.it tel +39 02 241 047 350